Gestetner

Cost-efficient and compact colour solutions



Colour flexibility for all office types

The demands on office document production rise ever higher. Colour use is increasingly becoming a standard, but document outsourcing eats away at your budget. Gestetner's MP C2030/MP C2530 constitute a welcome alternative. Productive, flexible and compact, these colour MFPs offer excellent value for your money. Discover how all the capabilities you require can fit inside a slim design.

- Sharp and high-quality colour output with new PxP™ toner.
- Excellent productivity at 20/25 ppm in both colour and B/W.
- · Duplexing at simplex speed.
- · Exceptionally wide media handling.
- All-round functionality: copying, printing, scanning and faxing (optional).



Covering your entire workflow



Superb colours

Your colour output will look crisp and accurate due to the MP C2030/MP C2530's PxP™ toner. Quality remains consistent even during longer runs. Print resolution is an excellent 600 dpi.

Wide media range

Creating reports, handouts or flyers? The MP C2030/MP C2530 handle a truly wide variety of paper types. They accept sizes between A3 and A6, from light (52 g/m² via the bypass tray) to heavy (256 g/m² via standard and bypass trays). Glossy and coated papers or card stock are processed effortlessly. Even envelopes and transparencies can conveniently be fed via the standard bypass tray.

Excellent productivity

Duplex printing at simplex speeds: not all machines can do it. The MP C2030/MP C2530 print and copy at 20/25 ppm in both monochrome and full colour. First copy speed is less than 6.5 seconds for B/W and less than 9.5 seconds for full colour.

Standard printing capabilities

The new MP C2030/MP C2530 have all basic printer features as standard. Enjoy their functionalities with the straightforward icon-based RPCS™ driver, or with the optional PCL driver. Your B/W copies can even be sorted electronically for extra convenience.

Reliable engines

The MP C2030/MP C2530's engines are the fruit of years of Gestetner expertise. Their new tandem 4-drums design ensures reliable operation. A simplified paper path reduces the risk of jams, and your machine is continuously available. With a maximum paper capacity of 1,600 sheets, refills are kept to a minimum.

We think green, and you?

'Green' is not just a colour for Gestetner – it is an attitude. Our PxP™ (polyester x polymerisation) toner is produced with significantly less carbon oxide emission than conventional toners. A more direct benefit for you is the MP C2030/MP C2530's standard duplex unit. Saving paper is kind to the environment as well as to the company budget.



MP C2030/MP C2530 Aficio

SPECIFICATIONS

COPIER				
Copying process:	Dry electrosta	Dry electrostatic transfer system		
Copy speed:	MP C2030:	B/W / full colour:	20 copies per minute	
	MP C2530:	B/W / full colour:	25 copies per minute	
Resolution:	600 dpi			
Multiple copy:	Up to 999			
Warm-up time:	Less than 25 seconds ¹			
First output speed:	Black and wh	ite: L	ess than 6.5 seconds	
	Full colour:	L	ess than 9.5 seconds	
Zoom:	25 - 400% (in 1% steps)			
Memory:	Standard:		512 MB	
Paper input capacity:	Standard:	2 x 2	250-sheet paper trays	
		1 x 1	00-sheet bypass tray	
	Maximum:		1,600 sheets	
Paper output capacity:	Maximum:		550 sheets	
Paper size:	A6 - A3			
Paper weight:	Paper tray 1:		60 - 256 g/m²	
	Paper tray 2:		60 - 169 g/m ²	
	Bypass tray:		52 - 256 g/m²	
	Duplex tray:		60 - 105 g/m²	
Dimensions (W x D x H):	587 x 655 x 8	45 mm (with ARDF)		
Weight:	Less than 100	Less than 100 kg (with ARDF)		
Power source:	220 - 240 V, 5	220 - 240 V, 50/60 Hz		
Power consumption:	Operation:		Maximum 1,680 W ¹	

	Duplex tray:
Dimensions (W x D x H):	587 x 655 x 845 mm (with ARDI
Veight:	Less than 100 kg (with ARDF)
ower source:	220 - 240 V, 50/60 Hz
ower consumption:	Operation:

PRINTER

Print speed:	MP C2030:	B/W / full colour: 20 prints per minute
	MP C2530:	B/W / full colour: 25 prints per minute
Printer language:	Standard:	RPCS™
	Option:	PCL5c, PCL6
Resolution:	600 dpi	
Interface:	USB 2.0 Host	
	USB 2.0 Device	ce
	Ethernet 10 ba	ase-T/100 base-TX
Network protocol:	TCP/IP (IPv4, IPv6), IPX/SPX	
Supported environments:	Windows [®]	2000/XP/Vista/Server 2003/Server 2008
		IBM iSeries
	AS	S/400 using OS/400 Host Print Transform



Scan speed:	B/W:	41 images per minute (LEF, A4)
	Full colour:	26 images per minute
Resolution:	Maximum 600 dpi	
Original size:	A5 - A3	
Bundled drivers:	TWAIN Network	

SOFTWARE

SmartDeviceMonitor™ Web SmartDeviceMonitor™ Web Image Monitor DeskTopBinder™ Lite/Professional/v.5

(FAX (option)

Circuit:	PSTN, PBX		
Compatibility:	ITU-T (CCITT) G3		
Modem speed:	Maximum 33.6 Kbps		
Resolution:	200 x 100/200 dpi		
Compression method:	MH, MR, MMR, JBIG		
Scanning speed:	36 sheets per minute		
Memory capacity:	Standard:	4 MB	
Memory backup:	Yes		

OTHER OPTIONS

500-sheet paper tray, 2 x 500-sheet paper trays, Caster table, Cabinet, Inner one bin tray, Side tray, PCL module, Fax unit, Fax stamp ink, Copy Data Security Unit, PictBridge, Counter interface unit type A, Key counter bracket, Remote communication gate BN1.

For availability of models, optional apparatus and software, please consult your local Gestetner supplier.















ISO9001: 2000 certified ISO14001 certified

Gestetner has designed these products to meet EC ENERGY STAR guidelines for energy efficiency.

All brand and/or product names are trademarks of their respective owners.

Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2008 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.

www.gestetner.com





¹ Warm-up time and power consumption may differ depending on the conditions