


Compact, economical multifunctionals

MP C300/MP C300sr/MP C400/MP C400sr Aficio




Save space, energy and costs

The MP C300/MP C300SR/MP C400/MP C400SR are productive, user-friendly solutions that are exactly what your office workflow requires. These compact colour multifunctionals copy, print, scan and fax efficiently and at high speed, with automatic duplex printing as standard. The MP C300SR/MP C400SR even staple your documents automatically. For maximum user convenience, the large colour touch-panel can be tilted to improve visibility. These devices smoothly integrate into your existing network and offer a low Total Cost of Ownership thanks to Quick Start technology and low power consumption.



- Excellent productivity: 30/40 pages per minute.
- User-friendly operation.
- Low Total Cost of Ownership.



Effective solutions



RAISE THE PACE

50 to 60 seconds. That is all it takes for the MP C300/MP C300SR/MP C400/MP C400SR to be ready for use. Colour and monochrome are printed at the same high speed of 30 (MP C300/MP C300SR) and 40 (MP C400/MP C400SR) pages per minute. And with a maximum paper capacity of 2,300 sheets, you enjoy long, undisturbed runs.



IMPROVE YOUR WORKFLOW

Distribute documents quickly by scanning to e-mail, FTP, SMB, URL or NCP. There is no need to switch on your computer: print directly from USB memory or SD card. Fax, e-mail, scan to folder and USB – all in one action.



KEEP COSTS DOWN

With their low Total Cost of Ownership, the MP C300/MP C300SR/MP C400/MP C400SR will save you money. Their Quick Start-up technology allows them to make maximum use of the energy-saver mode. As a result, their energy consumption is remarkably low. Your paper expenses are reduced with a standard automatic duplex unit.



_								. 1
	-	Ready			_	Store File	Check Mode	0
A								D
	olour Select I Colour	1 L A	2 8 0 4 A4	3 U 0 4		et bess		
	& White		Made Doo					
Text	Roto	Full Size Aut	feter/blaye	結:話 :	1212 E	93%	100%	
	t/Roto	Ta.m	2 (10 T T T T T T T T T T T T T T T T T T T		1.13			-
	thes _	<u>ura</u> ,	1. 1. L	3+12	1.0	Oraste M	790 G G	
4	o Density 🕨	990	9 0					
Post	ecial Original	Finishing	Cover/Ste Sheet	Edit / Col	ar Da.	Konton Sala	Refice / Bilar	
200			3	245	Job Ust		1 529 - 3818	
					2	3	٩	P
		6		4	5	6		
	2	6	-		8	9	C/0	\square
0!				-18	0			\square

EASY OPERATION

The MP C300/MP C300SR/MP C400/MP C400SR have been designed with their users' convenience in mind. Lightweight yet sturdy paper trays open and close smoothly. The operation panel can be tilted to improve visibility. The large colour touch-panel has a supremely user-friendly graphic user interface. Implementing jobs by changing detail settings like number of copies, B/W or F/C, duplex or simplex, is quick and easy, also from your computer.

SECURE WORKFLOWS

Exert control: ask authentication, lock prints, or hold them until a password is entered. Secure copy data: mask text, or prohibit the use of certain functions via the optional Copy Data Security Unit. Keep a close eye on colour usage by setting and managing the output of individuals and groups with quota setting.





ENVIRONMENTALLY FRIENDLY

At Gestetner we help you lower the environmental impact in your office as well as lowering your cost. The MP C300/MP C300SR/MP C400/MP C400SR have eco-friendly and money-saving features such as fast duplex printing and copying, ultra low sleep mode, increased toner yield and low TEC (Typical Electricity Consumption). In addition, Gestetner products are Energy star compliant. This means less C02 is produced in providing the energy needed to run Gestetner devices.

MP C300/MP C300sr/MP C400/MP C400sr Aficio

COPIER

Copying process: Copy speed:

Multiple copy: Warm-up time: First output speed:

Zoom: Memory: Paper input capacity:

ARDF capacity: Paper output capacity:

Paper size:

Paper weight:

Duplexing: Dimensions (W x D x H): Weight: Power source: Power consumption:

PRINTER

CPU: Print speed:

Printer language: Printer resolution:

Interface:

Memory: Network protocol: Supported environments:

Dry electrostatic transfer system with dual component development; 4-drum method Full colour: 30/30/40/40 copies per minute B/W: 30/30/40/40 copies per minute Up to 999 50/50/60/60 seconds Full colour: Less than 15 seconds B/W: Less than 10 seconds 25 - 400% (in 1% steps) Maximum: 1.5 GB + 160 GB Hard Disk Drive Standard: 1 x 550-sheet paper tray 100-sheet bypass tray Maximum: 2,300 sheets 50 sheets Standard: 500/250/500/250 sheets Maximum: 650/300/650/300 sheets Paper trays: A4 Bypass tray: 216 x 600 mm Paper trays: 52 - 220 g/m² Bypass tray: 52 - 256 g/m² Duplex tray: 60 - 163 g/m² Standard 550 x 570 x 710 mm (incl. ARDF) Less than 80/85/80/85 kg 220 - 240 V. 50 - 60 Hz Maximum: Less than 1.65 kW

Celeron M (1 GHz) Full colour: 30/30/40/40 prints per minute B/W: 30/30/40/40 prints per minute PCL5c, PCL6, Adobe® PostScript® 3™, XPS 600 x 600 dpi (1, 2, 4 bit) 1,200 x 1,200 dpi (1 bit) Standard: USB 2.0 (Type A & B), 10 base-T/ 100 base-TX Ethernet Option: 1000 base-T Gigabit Ethernet, Wireless LAN (IEEE802.11 a/g) 1 GB + 160 GB Hard Disk Drive TCP/IP (v4, v6), Bonjour PCL5c, PCL6: Windows® 2000/XP/Vista/7/ Server 2003/Server 2008/Server 2008R2 Citrix Metaframe XP/Presentation Server3.0. Presentation Server4.0/4.5, Citrix XenApp5.0 Adobe® PostScript® 3™: Windows® 2000/ XP/Vista/7/Server 2003/Server 2008/Server 2008R2. Citrix Metaframe XP/Presentation Server3.0, Presentation Server4.0/4.5, Citrix XenApp5.0, Macintosh OS 10.2x/10.4.x/10.5x XPS: Windows® Vista/7/Server 2008/Server 2008R2

∠ SCANNER

Scan speed: Resolution: Original size: Output formats: Bundled drivers: Scan to e-mail: Destination addresses: Stored destination addresses: Address book: Scan to folder: Destination: Full colour: 30 images per minute B/W: 30 images per minute Standard: 100 - 600 dpi Default: 200 dpi A5 - A4 TIF, JPEG, PDF Network, TWAIN SMTP authentication, POP before SMTP authentication Maximum 500 per job Maximum 500 per job Maximum 2,000 Via LDAP or locally on HDD SMB, FTP, NCP Maximum 100 folders per job

SOFTWARE

SmartDeviceMonitor™, Remote Communication Gate S Pro™, Web Image Monitor, DeskTopBinder™ Lite

(FAX (OPTION)

Circuit: Compatibility: Modem speed: Resolution: Compression method: Scanning speed: Memory backup: PSTN, PBX ITU-T, G3 Maximum: 33.6 Kbps Maximum: 400 x 400 dpi MH, MR, MMR, JBIG 0.8 seconds (200 x 100 dpi A4 SEF) Yes

OTHER OPTIONS

1 x 550-sheet paper tray, 2 x 550-sheet paper tray, Inner one bin tray (MP C300/ MP C400 only), Side tray, Output tray, Fax memory unit, Fax unit, HDD Encryption unit, Wireless LAN (IEEE802.11 a/g), 1000 base-T Gigabit Ethernet, Copy Data Security Unit, Remote communication gate, Data Overwrite Security Unit, Key counter interface unit, File Format Converter, Browser unit

Ricoh has designed these products to meet EC ENERGY STAR guidelines for energy efficiency.

For availability of models, options and software, please consult your local Gestetner supplier.







bled Selfsvare Architecture

lava

APictBridge

ISO9001 certified, ISO14001 certified, ISO27001 certified

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2013 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/ or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.



Gestetner

For more information, please contact

www.gestetner.com









